


Unsplit long arm



Split long arm

Range: 2500 Kg - 3500 Kg

- Rotating paper roll clamp for safe and effective vertical and horizontal roll handling.
- Slim and smooth arm and frame design, optimal visibility and advanced hydraulic operation.
- Pivoting arm movement. Short and long arms. Non-split long arm for single roll handling. Split arm for 1 - 2 roll handling.
- 180-degree rotation. Hydraulic cushioning in the vertical end positions.
- All hydraulic functions protected with built-in pressure relief valves and check valves. All service and maintenance points easily available.

Model	Capacity	Load Centre	Roll Range	Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	Q kg	BP mm	A mm	D mm	W Kg	HCG mm	VCG mm	LL mm	M x N mm	O mm	H mm	ISO 2328
Single roll clamps - Unsplit long arm												
AR-33RH-13F	3500	650	550-1300	1035	780	245	360	190	240x400	200	160	2 / 3 A
AR-33RH-13	3500	650	250-1300	1035	785	245	360	190	240x400	200	160	2 / 3 A
AR-33RH-14F	3250	700	600-1400	1035	800	269	360	190	240x400	200	160	2 / 3 A
AR-33RH-14	3250	700	250-1400	1035	805	269	360	190	240x400	200	160	2 / 3 A
AR-33RH-15F	3000	760	650-1520	1035	825	299	360	190	240x400	200	160	2 / 3 A
AR-33RH-15	3000	760	260-1520	1035	830	299	360	190	240x400	200	160	2 / 3 A
AR-33RH-16F	2800	800	700-1600	1035	835	312	360	190	240x400	200	160	2 / 3 A
AR-33RH-16	2800	800	270-1600	1035	840	312	360	190	240x400	200	160	2 / 3 A
AR-33RH-18F	2500	915	800-1830	1035	880	368	360	200	240x400	200	160	2 / 3 A
AR-33RH-18	2500	915	400-1830	1035	885	368	360	200	240x400	200	160	2 / 3 A
1 - 2 roll clamps - Split long arm												
AR-33RJ-13F	3500	650	550-1300	1035	770	239	360	190	240x400	200	160	2 / 3 A
AR-33RJ-13	3500	650	250-1300	1035	775	239	360	190	240x400	200	160	2 / 3 A
AR-33RJ-14F	3250	700	600-1400	1035	795	262	360	190	240x400	200	160	2 / 3 A
AR-33RJ-14	3250	700	250-1400	1035	800	262	360	190	240x400	200	160	2 / 3 A
AR-33RJ-15F	3000	760	650-1520	1035	815	292	360	190	240x400	200	160	2 / 3 A
AR-33RJ-15	3000	760	260-1520	1035	820	292	360	190	240x400	200	160	2 / 3 A
AR-33RJ-16F	2800	800	700-1600	1035	825	305	360	190	240x400	200	160	2 / 3 A
AR-33RJ-16	2800	800	270-1600	1035	830	305	360	190	240x400	200	160	2 / 3 A
AR-33RJ-18F	2500	915	800-1830	1035	870	361	360	200	240x400	200	160	2 / 3 A
AR-33RJ-18	2500	915	400-1830	1035	875	361	360	200	240x400	200	160	2 / 3 A

Notes:

- Two hydraulic functions required.
- Models AR-33RHF/RJF with fixed (non-moving) short arm.
- Models AR-33RH/RJ with hydraulically positionable short arm.
- Standard contact pads: cast pad with high-friction surface.
- Minimum 5-degree forward tilt on lift mast is required for horizontal handling.
- For 0-degree tilt, special arms are available. Consult Bolzoni Auramo

Options:

- Special roll ranges.
- Arm height D = 830 mm.
- Contact pad options:
 - steel-sprayed
 - rubber faced
 - polyurethane faced
 - full length contact pads.

